

< 縞 板 >

厚み		914X1829 (3'x6')	1219X2438 (4'x8')	1524x3048 (5'x10')
3.2mm		○	○	○
	枚単重	44.8	79.6	124
4.5mm		○	○	○
	枚単重	61.8	110	172
6mm		○	○	○
	枚単重	81.5	145	227
9mm		○	○	○
	枚単重	121	215	336

< 鋼 板 >

品名	枚単重	熱延鋼板	酸洗鋼板	電気メッキ
		SPHC	SPHC-P	SECC
PL 1.6X914X1829	21.0	○	○	○
PL 1.6X1219X2438	37.3	○	○	※○ 枚37.4kg
PL 1.6X1524X3048	58.3	○	○	○
PL 2.0X914X1829	26.3		○	
PL 2.0X1219X2438	46.7		○	○
PL 2.3X914X1829	30.2	○	○	○
PL 2.3X1219X2438	53.7	○	○	○
PL 2.3X1524X3048	83.9	○	○	○
PL 3.2X914X1829	42.0	○	○	○
PL 3.2X1219X2438	74.7	○	○	○
PL 3.2X1524X3048	117	○	○	○
PL 3.2X1524X6096	233	○		
PL 4.5X914X1829	59.1	○	○	
PL 4.5X1219X2438	105	○	○	
PL 4.5X1524X3048	164	○		
PL 4.5X1524X6096	328	○		
PL 6X914X1829	78.8	○	○	
PL 6X1219X2438	140	○	○	
PL 6X1524X3048	219	○		
PL 6X1524X6096	438	○		
PL 9X914X1829	118	○		
PL 9X1219X2438	210	○		
PL 9X1524X3048	328	○		
PL 12X914X1829	158	○		
PL 12X1219X2438	280	○		
PL 12X1524X3048	438	○		
PL 16X914X1829	210	○		
PL 16X1219X2438	373	○		
PL 19X914X1829	249	○		
PL 19X1219X2438	443	○		
PL 22X914X1829	289	○		
PL 22X1219X2438	513	○		
PL 25X914X1829	328	○		
PL 25X1219X2438	583	○		

<橋梁用形鋼>

規格: SMA490AW

溶接構造用耐候性熱間圧延鋼材

JIS G 3114

品名	m単重	5.5	6	7	8	9	10	11	12
アンゲル									
L 9X75X75	9.96	54.8	59.8	69.7	79.7	89.6	99.6	110	○ 120
L 10X90X90	13.3	73.2	79.8	93.1	106	120	133	146	○ 160
L 10X100X100	14.9	82.0	89.4	104	119	134	149	164	○ 179
L 12X130X130	23.4	129	140	164	187	211	234	257	○ 281

<SS400鋼板>

厚み		914X1829	1219X2438	1524X3048
2.3mm	枚単重	30.2	53.7	83.9
			○	○
3.2mm	枚単重	42.0	74.7	117.0
			○	○
4.5mm	枚単重	59.1	105.0	164.0
			○	○
6mm	枚単重	78.8	140.0	219.0
			○	○
9mm	枚単重	118.0	210.0	328.0
			○	○
12mm	枚単重	158.0	280.0	438.0
			○	○